

Fluke i1010

AC/DC Current Clamp



AC/DC Current clamps for DMM's

Fluke Current clamps are the ideal tools to extend the current ranges of Fluke tools.

- Battery-powered Hall-effect probe measures 1 A to 1000 A
- 1 mV/Amp output guarantees easy reading on your meter
- Take accurate current readings without breaking the circuit

Specifications	
Measurement type	Hall sensor
Nominal current range	600 A, AC 1000 A, DC
Continuous current range	1 A - 600 A, AC 1 A - 1000 A, DC
Maximum Non-Destructive Current	1000 A
Lowest measurable current	0.5 A
Basic Accuracy	2% + 0.5 A (% reading + floorspec)
Useable frequency	DC - 10 kHz
Output level(s)	1 mV/A
Zero error adjustment	Yes

Safety Specifications	
Safety	CAT III, 600 V
Maximum voltage	600 V

Mechanical & General Specifications	
Warranty	1 year
Battery Life	9 V, 60 h
Maximum conductor diameter	30 mm 2 x 25 mm
Output cable length	1.6 m
Shrouded banana plugs	Yes



敏盛企業有限公司

<http://www.mavin.com.tw>

TEL:03-5970828 FAX:03-5972622 新竹湖口工業區工業四路3號2F