

PINTEK

AC/DC Current Probe


★ **DC~1.5MHz**
1mA~40ADC / 80Ap-p

High Sensitivity!



PA-699

- Max. $\pm 40\text{ADC}/80\text{Ap-p}$
- Sensitivity: $\geq 1\text{mA}$
- Bandwidth: DC~1.5MHz
- Rise Time: $0.23\mu\text{S}$
- Over Range Function
- 1V/A, 0.1V/A Range
- Adaptor/Battery Input
- Separating Design, Convenient Durable



敏盛企業有限公司

MAVIN METROLOGY EN.CO.,LTD


TEL:03-5970828 FAX:03-5972622

地址：新竹縣湖口鄉工業四路3號2F

<http://www.mavin.com.tw>





PA-699 AC/DC Current Probe



SPECIFICATIONS:

FUNCTION/MODEL	PA-699
Accuracy Typical	±3%: 10mA~8A peak at 1V/A ±4%: 100mA~80A peak at 0.1V/A
Max. Working Voltage	300V CAT III
Max. Sensitivity	≥ 1 mA
Frequency Range	DC-1.5MHz(-3dB)
Rise Time	0.23 μS
Battery or Adaptor	9V NEDA 1604A, IEC DLR61 or PINTEK Specified Adaptor
Accessories	BP-250, MT-246N, Adaptor, Instruction Manual.

Waveform Comparison Between PA-699 And Other Brand In Market:



ACCESSORIES:



免責聲明

資料僅供參考，若有與原廠不合之處，請以原廠規格為準，且不供任何證明文件之用