



### FEATURES:

- Right Angle BNC Provided for Easy Access
- Lengths other than those specified are available upon request.

### MATERIALS:

- Conn: 1<sup>st</sup> End – Right Angle BNC Male.  
 Body and Fittings: Tarnish Resistant.  
 Center Contact: Gold Plated per MIL-C-39012.
- Cable: RG58C/U. (.195) O.D.  
 50 Ohms Impedance  
 Marking: "POMONA 1383-C-XX".
- Conn: 2<sup>nd</sup> End-BNC Male.  
 Body Fittings: Non-tarnish finish.  
 Center Contact: Gold Plated per MIL-C-39012.

### RATINGS: Entire Assembly

- Operating Temperature: +50°C. (+122°F.) Max.  
 Operating Voltage: Shield-Earth: 30VAC/60VDC Max.  
 Inner conductor-Shield: 500 VRMS Max.

### ORDERING INFORMATION: Model 1383-C-XX

XX=Cable Length, Standard Lengths: 18" (457), 24" (610), 36" (914), 48" (1219), 60" (1524)

Ordering Example: 1383-C-60 indicates 60" (1524)

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ± .005" (.127 mm).  
 All specifications are to the latest revisions. Specifications are subject to change without notice.  
 Registered trademarks are the property of their respective companies. Made in USA