



### Features:

- All 12 adapters in kit are direct. **No intermediate couplers.**
- Reduced signal loss in adapters due to absence of couplers.
- Kit includes the most frequently used N Type adapters including N / N, N / SMA, N / BNC, and N Terminations, both 50 and 75 ohm. See complete list in drawing or in table below.
- Rugged, lockable, pistol-grip case.
- All parts precision machined brass with tarnish resistant gold or nickel plating.
- Male center pins are gold plated brass.
- Female contacts are gold plated heat treated beryllium copper.
- Insulation material is high density PTFE.



**Order Example: 72932  
(N Adapter Kit)**

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ±.005" (.127 mm).  
All specifications are to the latest revisions. Specifications are subject to change without notice.  
Registered trademarks are the property of their respective companies.

Sales: 800-490-2361 Fax: 888-403-3360 Technical Support: 800-241-2060 (technicalsupport@pomonatest.com)  
For "Where to Buy" information, visit the Pomona web site at [www.pomonaelectronics.com](http://www.pomonaelectronics.com)

| Item | Description                 | Pomona Part Number | NOM. IMPEDANCE | FREQ. RANGE   | VSWR              | OPERATING TEMP   |
|------|-----------------------------|--------------------|----------------|---------------|-------------------|------------------|
| 1    | TYPE N female/male RA       | 3843               | 50 Ohms        | DC to 11GHz   | 1.35 to 11GHz     | - 65° to +165° C |
| 2    | TYPE N Terminator plug      | 4240-75            | 75 Ohms        | DC to 500 MHz | 1.35 at 500 MHz   | - 65° to +165° C |
| 3    | TYPE N Terminator plug      | 4240-50            | 50 OHMS        | DC to 500 MHz | 1.35 at 500 MHz   | - 65° to +165° C |
| 4    | TYPE N female/female        | 3841               | 50 Ohms        | DC to 11GHz   | 1.35 to 11GHz     | - 65° to +165° C |
| 5    | BNC male/ TYPE N female     | 3535               | 50 Ohms        | DC to 4 GHz   | 1.35 to 4 GHz     | - 65° to +165° C |
| 6    | BNC female, TYPE N male     | 3288               | 50 Ohms        | DC to 4 GHz   | 1.35 to 4 GHz     | - 65° to +165° C |
| 7    | SMA Termination male        | 4286               | 50 Ohms        | DC to 18GHz   | 1.25 Max at 18GHz | - 65° to +165° C |
| 8    | TYPE N male/ TYPE N male    | 3842               | 50 Ohms        | DC to 11GHz   | 1.35 to 11GHz     | - 65° to +165° C |
| 9    | TYPE N female/female/female | 5089               | 50 Ohms        | DC to 11GHz   | 1.35 to 11GHz     | - 65° to +165° C |
| 10   | SMA female/ TYPE N female   | 4299               | 50 Ohms        | DC to 11GHz   | 1.35 to 11GHz     | - 65° to +165° C |
| 11   | SMA male/TYPE N female      | 4298               | 50 Ohms        | DC to 11GHz   | 1.35 to 11GHz     | - 65° to +165° C |
| 12   | SMA female/TYPE N male      | 4297               | 50 Ohms        | DC to 11GHz   | 1.35 to 11GHz     | - 65° to +165° C |

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ± .005" (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies.

Sales: 800-490-2361 Fax: 888-403-3360 Technical Support: 800-241-2060 (technicalsupport@pomonatest.com)

For "Where to Buy" information, visit the Pomona web site at [www.pomonaelectronics.com](http://www.pomonaelectronics.com)