

Active Probe

P7225 Data Sheet



Features & Benefits

- <math><140\text{ ps}</math> Rise Time (guaranteed)
- 2.5 GHz Bandwidth
- $\leq 0.8\text{ pF}$ Input Capacitance
- 8 $V_{\text{pk-pk}}$ Dynamic Range
- 40 $k\Omega$ Input Resistance
- TekConnect® Interface
- Supports TDS7154/7254 Active Probe Needs by Providing a TekConnect 2.5 GHz, 8 $V_{\text{pk-pk}}$ Dynamic-range Cost-effective Probing Solution for Mid-band Real-time Oscilloscopes
- 10x Attenuation

Applications

- Verification, Debug, and Characterization of High-speed Designs
- Design, Development, and Compliance Testing
- Signal Integrity, Jitter, and Timing Analysis
- Manufacturing Engineering and Test
- Signals with Voltage Swings up to 8 $V_{\text{pk-pk}}$

Selecting the right probe for your application is key to attaining the best signal fidelity in your measurements. Active probes provide truer signal reproduction and fidelity for high-frequency measurements. With our ultra-low input capacitance and high input resistance provided by the P7225, you are able to make measurements with minimal signal distortion. This probe offers a wide 8 $V_{\text{pk-pk}}$ dynamic range to access today's voltage levels.

Performance You Can Count On

Depend on Tektronix to provide you with performance you can count on. In addition to industry-leading service and support, this product comes backed by a one-year warranty as standard.

Characteristics

Physical Characteristics

Rise Time – <140 ps.
 Bandwidth – 2.5 GHz.
 Attenuation – 10x.
 DC Resistance – 40 kΩ.
 Input Capacitance – ≤0.8 pF.
 Dynamic Range – ±4 V.
 Offset Range – ±10 V.
 Interface – TekConnect®.

Ordering Information

Included Accessories – One-year warranty, plus the following:

| Product Name/Description | Part Number | Quantity |
|--|-------------|----------|
| Ground lead kit – 3 in. and Y Lead Adapter | 196-3456-xx | 1 Each |
| SMT KlipChip™ Adapter | 206-0364-xx | 1 |
| 5 Colors, Color Coding Clips | 016-1315-xx | 1 |
| Pogo Pin Ground (set of 10) | 016-1772-xx | 1 |
| Square Pin Sockets (set of 10) | 016-1773-xx | 1 |
| Customizable Ground Lead (set of 5) | 196-3482-xx | 1 |
| Probe Tips (set of 10) | 131-5638-xx | 1 |
| SureToe™ Adapter (set of 12) | ST501 | 1 |
| Instruction Manual | 071-1186-xx | 1 |
| Probe Carrying Case | 016-1879-01 | 1 |
| Accessory Case | 006-7164-xx | 1 |
| Wrist Strap | 006-3415-04 | 1 |
| Certificate of Traceability | – | 1 |

Service

Opt. C3 – Calibration Service 3 Years.
 Opt. C5 – Calibration Service 5 Years.
 Opt. D1 – Calibration Data Report.
 Opt. D3 – Calibration Data Report 3 Years (with Opt. C3).
 Opt. D5 – Calibration Data Report 5 Years (with Opt. C5).
 Opt. R3 – Repair Service 3 Years.
 Opt. R5 – Repair Service 5 Years.

Recommended Accessories

SMK4, IC Grabber – Order 013-0309-xx (set of 2).



Tektronix is registered to ISO 9001 and ISO 14001 by SRI Quality System Registrar.